V7 USB 2.0 CABLES

V7 High-Speed USB cables are designed to connect computer peripherals such as digital cameras, printers, scanners, personal media players, external high disk drives, flash drives and network adapters. The V7 USB 2.0 cables support data transfer up to 480 mbps and are backward compatible with USB 1.0 and 1.1 devices. These fully shielded USB cables feature high-grade PVC jacket construction combined with shielded twisted pair data-lines, providing excellent performance.

A popular selection of V7 USB Cables:

Length	Model Number	Product Description
6 ft /1.8 m	V7N2USB2AB-06F	V7 USB 2.0 Device Cable A-B Black
10 ft /3 m	V7N2USB2AB-10F	V7 USB 2.0 Device Cable A-B Black
16 ft /4.8 m	V7N2USB2AB-16F	V7 USB 2.0 Device Cable A-B Black
3 ft /0.9 m	V7N2USB2EXT-03F	V7 USB Passive Extension Cable USB A to A (m/f) Black
6 ft /1.8 m	V7N2USB2EXT-06F	V7 USB Passive Extension Cable USB A to A (m/f) Black
10 ft /3 m	V7N2USB2EXT-10F	V7 USB Passive Extension Cable USB A to A (m/f) Black
3 ft /0.9 m	V7N2USB2AMCB-03F	V7 Micro-USB 2.0 Device Cable USB A to USB Micro-B Black
6 ft /1.8 m	V7N2USB2AMCB-06F	V7 Micro-USB 2.0 Device Cable USB A to USB Micro-B Black

Specifications

Performance:	Data transmission up to 480 Mbps
Color:	Black
Connectors:	Gold-flashed connector contacts, nickel-plated shell
Cable Jacket:	PVC
Compliance:	RoHS Compliant
Country of origin:	China
Warranty:	Lifetime Warranty against material defects and workmanship

USB AB Cable

USB Extension Cable

Micro USB Cable

For a complete list of V7 products, Please visit our website www.ingrammicro.com/V7 or contact your Ingram Micro Sales Representative at 800-456-8000.

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions, are disclaimed. Measurement standards and testing conditions, as per manufacturer definitions, are available on request. 02/28/2011